



TLI-BLO6/12

SLIMLINE BATTEN
USABLE INDOOR AND OUTDOOR

TECHNICAL

Materials of Optics	-
Materials of Housing	Plastic
Light Source	CREE/Osram
Color Temperature	3000/5500k
Luminous Efficiency@4000K	80Lm/W
CRI	>85
Beam Angle(°)	95°
UGR	-
Lifetime(hr)	50,000h
Product Finishing	White



FEATURES & BENEFITS

CCT Selection DIP Switch	-
LED Driver	Built-in
Dimming Option	N/A
Functions	-
Ingress Protection (IP Rating)	IP20/IP 65
Impact Resistance (IK Rating)	-
Power Factor (PF)	≥0.9
Certification	SAA/RoHS/CE/CB

INSTALLATION & ACCESSORIES



DATA SHEET

CODE	WATT	INPUT VOLTAGE	DIMENSION(mm)	Color Temperature	LUMEN
TLI-BL12-45W-WW-IP20	45W	AC200-240	1210x78x28	3000K	3490lm
TLI-BL12-45W-CW-IP20	45W	AC200-240	1210x78x28	5500K	3750lm
TLI-BLO6-24W-WW-IP20	24W	AC200-240	600x78x28	3000K	1760lm
TLI-BLO6-24W-CW-IP20	24W	AC200-240	600x78x28	5500K	1950lm
TLI-BL12-40W-WW-IP65	40W	AC200-240	1210x78x28	3000K	3800lm
TLI-BL12-40W-CW-IP65	40W	AC200-240	1210x78x28	5500K	4000lm