



# TLI-LOY

## OYSTER LIGHT

### TECHNICAL

|                      |                          |
|----------------------|--------------------------|
| Materials of Housing | Steel+Diffuser           |
| Light Source         | CREE/Osram               |
| Color Temperature    | 3000/4000/5000/5700k     |
| Luminous             | 106Lm/W                  |
| CRI                  | >85                      |
| Beam Angle(°)        | 24,36,60°                |
| Lifetime(hr)         | 40,000h                  |
| Product Finishing    | White/Black/Silver Frame |

### FEATURES & BENEFITS

|                                |                    |
|--------------------------------|--------------------|
| CCT Selection DIP Switch       | 3CCT               |
| LED Driver                     | Built-in           |
| Dimming Option                 | Triac/ DALI/ 0-10V |
| Ingress Protection (IP Rating) | IP 40/IP 54        |
| Power Factor (PF)              | ≥0.9               |
| Certification                  | SAA/RoHS/CE/CB     |

### DATA SHEET

| CODE           | WATT | INPUT VOLTAGE | DIMENSION(mm) | LUMEN(±5%) |
|----------------|------|---------------|---------------|------------|
| TLI-LOY-12-18W | 18W  | AC200-240V    | Ø300x40       | 2060lm     |
| TLI-LOY-12-25W | 25W  | AC200-240V    | Ø300x40       | 2650lm     |
| TLI-LOY-16-30W | 30W  | AC200-240V    | Ø400x52       | 3360lm     |



### DIMENSION

