













Classic COB: 08C

Introduction

- TLI COB downlight is uniquely designed with reflector and COB high power LED chip.
- Anti-glare lens plus Sharp COB LED, adjustable smart ring for different cutout sizes.
- AL6063 Aluminum profile provides excellent thermal dissipation.
- Isolated driver solution in dimmable achieves stable working performance.
- Application: Suitable for commercial and residential applications like offices, supermarkets, shops, schools, hotels, restaurants, workshop, warehouse, homes etc.

Appearance Parameters

Model	Dime	ension (r	nm)	Product Size	Cut out	Net Weight	
	Α	В	С	(mm)	(mm)	(kg)	
TLI-DN08C-10W	Ø110	Ø60	86	Ø110x86	Ø7090	0.38	

Technical Specifications

Voltage: AC100-240V / AC200-240V Lifespan: 40000hrs

Power: 10W / 13W / 15W CRI: ≥80
Power Factor: ≥0.9 IP: 20

Beam angle: 36° / 60° Dimmable: Triac dimmable CCT: 2700K 3000K 4000K 5000K Surface color: White / Silver

CC1: 2700K 3000K		Surface color: White / Silver							
Model	Non-DIM Lumen (±5%)				DIM Lumen (±5%)				
	2700K	3000K	4000K	5000K	2700K	3000K	4000K	5000K	
TLI-DN08C-10W	880	920	940	990	810	850	860	910	

