

TLI-BL

LED EMERGENCY QUICK FITTING BATTEN

TECHNICAL

Materials of Optics	Pmma Diffuser Wire Guards
Materials of Housing	Steel
Light Source	SMD
Color Temperature	6000K
Luminous Efficiency@4000K	100Lm/W
CRI	>85
Beam Angle(°)	120 °
Lifetime(hr)	50,000h
Product Finishing	White



FEATURES & BENEFITS

LED Driver	Built-in
Ingress Protection (IP Rating)	IP 20
Power Factor (PF)	≥0.9
Certification	SAA/RoHS/CE/CB

DATA SHEET

CODE	WATT	INPUT VOLTAGE	DIMENSION(mm)	DESCRIPTION	LUMEN
TLI-BL1200B-36EM-D	42W	AC200-277V	1228x125x91	emergency 4 foot double tube batten with diffuser	3600lm
TLI-BL1200B-36EM-W	42W	AC200-277V	1228x125x91	emergency 4 foot double tube batten with wire	3600lm
TLI-BL0600B-18EM-D	22W	AC200-277V	618x125x91	emergency 2 foot double tube batten with diffuser	1800lm
TLI-BL0600B-18EM-W	22W	AC200-277V	618x125x91	emergency 2 foot double tube batten with wire	1800lm

OPTICS



INSTALLATION & ACCESSORIES

