



TLI-TR06-25

TRACK LIGHT

TECHNICAL

Materials of Housing	Aluminium
Light Source	CREE Osram
Color Temperature	3000/4000/5700K
Luminous Efficiency@4000K	100lm/W
CRI	>85
Beam Angle(°)	15/24/30/45/60°
Lifetime(hr)	40,000h
Product Finishing	Black/White

FEATURES & BENEFITS

LED Driver	Built-in
Dimming Option	Triac/ DALI/ 0-10V
Ingress Protection (IP Rating)	IP 20
Power Factor (PF)	≥0.9
Certification	SAA/RoHS/CE/CB

DATA SHEET

CODE	WATT	INPUT VOLTAGE	DIMENSION(mm)	LUMEN(±5%)
TLI-TR06-25W	25W	AC100-240V	Ø90x121x233x141	2500Lm
TLI-TR06-35W	35W	AC100-240V	Ø110x131x234x161	3600Lm

- ▶ 15° 24° 30° 45° 60°
- ▶ 360° 180°
- ▶ IP20
- ▶ Flicker Free
- ▶ AC 100-240V PF≥0.9 CRI≥80 CRI≥90 CRI≥97
- ▶ SAA RoHS CE TÜV SÜD

INSTALLATION & ACCESSORIES

