



TLI-DN214

SMD DOWNLIGHT

TECHNICAL

Materials of Optics	PC
Materials of Housing	Aluminum
Light Source	COB (SDCM<3)
Color Temperature	3000/4000/5000K
Luminous Efficiency@4000K	90lm/W
CRI	>90
Beam Angle(°)	24°/45°
UGR	<19
Lifetime(hr)	50,000H
Product Finishing	White

FEATURES & BENEFITS

CCT Selection	3CCT
LED Driver	Built-in
Dimming Option	Triac 0-10v/DALI
Ingress Protection (IP Rating)	IP65
Impact Resistance (IK Rating)	IK10
Power Factor(PF)	≥ 0.9
Certification	SAA/ RoHS/CE

DATA SHEET

CODE	WATT	INPUT VOLTAGE	DIMENSION(mm)	CUT-OUT(mm)
TLI-DN214-A	7w/12w/18w	AC220-240V		
TLI-DN214-B	7w/12w/18w	AC220-240V		
TLI-DN214-C	7w/12w/18w	AC220-240V	7W Ø69x85mm	7W Ø55mm
TLI-DN214-D	7w/12w/18w	AC220-240V	12W Ø90x105mm	12W Ø75mm
TLI-DN214-E	7w/12w/18w	AC220-240V	18W Ø110x125mm	18W Ø95mm
TLI-DN214-F	7w/12w/18w	AC220-240V		

EXPERIENCE



INSTALLATION & ACCESSORIES

