



TLI-DN218

TECHNICAL

Materials of Optics	PC
Materials of Housing	Aluminum
Light Source	CREE
Color Temperature	3000/4000/5000K
Luminous Efficiency@4000K	90lm/W
CRI	≥90
Beam Angle(°)	36°
UGR	<19(24°)
Lifetime(hr)	50,000H
Product Finishing	White / Black

EXPERIENCE



FEATURES & BENEFITS

CCT Selection	3CCT
LED Driver	Built-out
Dimming Option	Triac/0-10v/DALI
Ingress Protection (IP Rating)	IP65
Impact Resistance (IK Rating)	IK06
Power Factor(PF)	≥ 0.9
Certification	SAA/ RoHS/CE

INSTALLATION & ACCESSORIES



DATA SHEET

CODE	WATT	INPUT VOLTAGE	DIMENSION(mm)	CUT-OUT(mm)	LUMEN(±5%)
TLI-DN218-IP65-3W	3W	AC200-240V	Ø90x90mm	Ø75mm	210lm
TLI-DN218-IP65-5W	5W	AC200-240V	Ø90x90mm	Ø75mm	415lm
TLI-DN218-IP65-7W	7W	AC200-240V	Ø90x90mm	Ø75mm	620lm
TLI-DN218-IP65-10W	10W	AC200-240V	Ø90x90mm	Ø75mm	895lm
TLI-DN218-IP65-12W	12W	AC200-240V	Ø90x90mm	Ø75mm	1055lm